
Copies may be obtained from the Canada Map Office, Department of Energy, Mines and Resources, Ottawa, or your nearest map dealer.

© Canada Copyrights Reserved 1975



WEST OF FOURTH MERIDIAN-OUEST DU QUATRIÈME MÉRIDIEN

Metres 1000 0 1000 2000 3000 4000 Mètres

Yards 1000 0 1000 2000 3000 4000 Verges

Miles 1 0 1

Scale 1:50,000 Echelle

CONTOUR INTERVAL 25 FEET Elevations in Feet above Mean Sea Level North American Datum 1927 Transverse Mercator Projection

ÉQUIDISTANCE DES COURBES 25 PIEDS Élévations en pieds au-dessus du niveau moyen de la mer Système de référence géodésique nord-américain, 1927 Projection transverse de Mercator

loose or stabilized surface, all weather... gravier aggloméré toute saison... 2 lanes or more losse surface, dry weather and de gravier. temps sec et unclassified streets..... rues hors classe.....

cart track...... de terre...... de terre.....

trail or portage...... sentier ou portage......

DEPOSIT CHARACTERISTICS **GENERAL COMMENTS**

| | Deposit Number | Material Reserves (1000 m³) Description Gravel Sand | | 0 m³) | Additional Comments | Texture (%) Gravel Sand Fines | | | (%) Wear | Overburden Thickness (m) | Deposit Thickness (m) | Deposit Area (ha) | Deposit Genesis | Additional Comments |
|---|-------------------|--|--------|-------|--|---|--------------------|------------------|-------------|--------------------------------|-----------------------------|-------------------------|------------------------|--|
| 1 | | | Graver | Jana | | - | - | | | | | | | |
| | 1 | Sandy gravel and gravel | 4763 | 2460 | Gravel coarse and fine; sand fine to coarse grained. | 47.9 to 79.0 | 20.0 to 45.7 | 1.0 to 6.4 | - | O to 2.1 | 2.4-7.6 Avg. 4.6 | 485 | . Recent alluvial | Deposit continues on NTS 83H/15. |
| | 2 | Sandy gravel | 10170 | 46650 | Gravel coarse and fine; sand coarse to fine grained, clean. | 57.5 to 77.5 | 21.1 to 40.5 | 0.4 to 1.4 | _ | 0 | 1.5 to 7.6 Avg. 3 | 4920 | Valley train | Deposit continues on NTS 82H/12. |
| | 3 | Sandy gravel | 980 | 420 | Sand fine to coarse, clean; gravel mainly fine. | ≃70 | ≃30 | ≃0 | 1 | 0 | 10.7 | 24 | Outwash | Deposit continues on NTS 82H/12. |
| | 4 | Sandy gravel | 10450 | 6650 | Gravel coarse and fine; sand fine and medium grained, silty, moderately clean. | ≃55 | ≃35 | ≃10 | - | 1 to 2 | More than 7 | 365 | Preglacial alluvial | |
| | 5 | Sandy gravel | 10810 | 10465 | Gravel coarse; sand fine and medium grained, silty, moderately clean. | 37 to 55 | 35 to 54 | 5 to 10 | - / | 0.6 to 6 Avg. 1.5 | 5.5 to 9 Avg. 7.5 | 285 | Preglacial alluvial | |
| | 6 | Sandy gravel | 1738 | 708 | Gravel coarse and fine; sand medium grained. | 69.5 | 28.3 | 2.2 | - | - | 1 to 2.1 Avg. 1.5 | 160 | Valley train | |
| | 7 | Gravel | 544 | 167 | Gravel coarse and fine; sand fine and medium grained, clean. | 75.6 | 23.2 | 1.2 | - | - | 1.8 to 3 Avg. 2.1 | 35 | Valley train | |
| | 8 | Gravel | 1875 | 625 | Gravel coarse and fine with some sand, fine and medium grained, clean. | ≃75 | ≃25 | ≃0 | - | - | 1.5 | 305 | Valley train | |
| | 9 | Gravelly sand | 525 | 975 | Gravel fine; sand fine grained. | ≃35 | ≃65 | ≃0 | - | 0.6 to 1.5 | 4 | 100 | Recent alluvial | |
| | 10 | Sandy gravel | 19560 | 9420 | Gravel coarse and fine; sand fine to coarse grained. | 65.2 | 31.4 | 3.4 | - | 0 to 1.8 | 1.8 to 4 Avg. 2.4 | 1400 | Recent alluvial | Deposit continues on NTS 82H/6. |
| | 11 | - | - | - | Assumed on basis of surface mapping or airphoto interpretation. | - | - | - | - | - | - | - | Recent alluvial | |
| | 12 | - | `- | - | Recorded in testholes and well logs. | - | - | - | - | - | - | - | - | Gravel and sand covered by more than 10 feet overburden. |
| | | | | | | | | | | | | | | |
| | | | | | *** , ¥2 | | ē. | | | | C C 20 4 | | | |

Deposit Number - Granular deposits shown on this map may have commercial possibilities.That assumption followed from two criteria used in the mapping process: study of the area considered only granular deposits greater than one metre thick, and covering an area more than one hectare; and it only considered deposits where the mineral-aggregate thickness was greater than the overburden thickness. Although the scale of mapping did not permit investigation of all small deposits, many small deposits containing existing pits are indicated.

Material Description - Sand and gravel has a variety of applications, such as concrete for construction, asphalt concrete, subbase and base course aggregate for roads, gravel and sand for road surfaces, and pit run for fill. Gradation, rock hardness, and binding characteristics, are some of the specific qualities that are considered in aggregate towards determining its end use. This map indicates these, and other, geological qualities of the sand and gravel within each deposit, but does not indicate their potential uses. The terms used in the table are defined in the figure below.

Reserves — The method of calculating in cubic metres the aggregate reserves of deposits took four basic steps. First, the area, in hectares, of each deposit was determined using aerial photographs. Second, geological interpretation, sometimes supported by subsurface information, was assumed in determining the geometry of each deposit, to estimate an overall, average deposit thickness in metres. Third, geological study and limited sample analyses determined the texture (gradation) of sediments in the deposit, and an overall average percentage of gravel and sand. Finally, the volume was calculated as follows: reserve gravel (m³) = area (ha) × thickness (m) × 10,000 × % gravel; the same formula was used for sand.

Texture — The texture of the sediment refers to the percentage of particles of various sizes. For mineral aggregate, the most important fractions are the gravel and sand. The actual dimensions of the clasts and particles in these fractions are given in the figure. The values given for a particular deposit were determined from a field estimate, or from laboratory analysis, of one or more samples from that deposit. Where more than one sample is taken the tabulated number is the mean value.

Wear — The resistance of gravel-size clasts to wear or abrasion can be measured in a laboratory test (ASTM-C131, Los Angeles Abrasion Testing). The amount of material that breaks down into smaller sizes is measured and related to the original sample weight in terms of percent wear. The higher the percentage wear the more susceptible the gravel is to breakdown under stress. Gravel with a percentage wear of less than 40 is considered very resistant.

Overburden Thickness — The thickness of non-economic material, or overburden, covering a deposit, sometimes is a limiting factor in the exploitation of an aggregate deposit. The tabulated values given are approximate overburden thicknesses as determined from geological investigations and subsurface testing.

3 Deposit number

Ces cartes sont en vente au Bureau des Cartes du Canada, ministère de l'Énergie, des Mines et des Ressources, Ottawa, ou chez le vendeur le plus près.

© Canada 1975, tous droits réservés

Assumed boundary

Active or inactive pit


Sand or gravel exposure

// Buried sand or Gravel deposit

Alberta Geological Survey test hole

Deposit Area — Deposits in this study were delineated by interpretation of aerial photographs and the contacts should be considered approximate. Information is precise only where test holes, or geological sections, are indicated.

Deposit Genesis — The genesis, or formation, of deposits is vital to the understanding of the gradational nature, extent and geometry of the deposit. This understanding forms the basis for extrapolation from a limited number of known points (test holes, pits, sections) and permits an







Alberta Geological Survey

This is a sand and gravel resource map prepared by the Alberta Geological Survey as part of a series at a scale of 1:50,000. The series represents an ongoing aggregate inventory of Alberta which provides data for general land-use planning, land management or aggregate exploration. Please note that the delineation of deposits and calculation of reserves are approximations only. Alberta Energy and Natural Resources provides financial support for the Aggregate Inventory.

Geology and compilation by I. Shetsen; revised from Earth Sciences

AGGREGATE RESOURCES FORT MACLEOD 82H/11